

TOKU 



CONSTRUCTION & INDUSTRIAL TOOLS

Ver 2.02

TOKU PNEUMATIC CO., LTD.
www.toku-net.co.jp/en

PAVING BREAKERS & TRENCHER

TPB TRC FEATURES

- High technology to front head design provides excellent durability and low maintenance cost.
- Alloy steel forgings provide maximum durability.
- Four bolt back head design stands up in rugged use.
- Latch type forged retainer for quick change
- Noise reduction muffler is optionally available.



TPB-30



TPB-40



TPB-60

OPTIONAL MUFFLER

TPB-30



TPB-40



TPB-60
TPB-73
TPB-90





TPB-73



TPB-90

TRENCHER



TRC-30

SPECIFICATION

| MODEL | CHUCK SIZE inch | STROKE inch (mm) | BORE inch (mm) | IMPACT RATE B.P.M. | WEIGHT lb (kg) | LENGTH inch (mm) | AIR CONSUMPTION CFM (m ³ /min) | AIR INLET inch | HOSE SIZE inch (mm) |
|--------|----------------------|---------------------|-------------------|-----------------------|-------------------|---------------------|--|-------------------|------------------------|
| TPB-30 | 7/8x3-1/4 or 1x4-1/4 | 3-3/8(85) | 1-3/4(44.45) | 1,550 | 33(15) | 22-1/4(564) | 49(1.4) | 3/8 NPT | 1/2(12.7) |
| TPB-40 | 1x4-1/4 | 5-3/4(146) | 1-3/4(44) | 1,100 | 40(18) | 26(660) | 50(1.3) | 1/2 NPT | 3/4(19) |
| TPB-60 | 1-1/8x6 or 1-1/4x6 | 4(100) | 2-1/4(57.15) | 1,400 | 66(30) | 25-3/8(645) | 70(2) | 3/4 NPT | 3/4(19) |
| TPB-73 | 1-1/8x6 or 1-1/4x6 | 5-5/16(144) | 2-1/4(57.15) | 1,200 | 70(31) | 27-3/16(690) | 63(1.8) | 3/4 NPT | 3/4(19) |
| TPB-90 | 1-1/8x6 or 1-1/4x6 | 6(152) | 2-5/8(66.67) | 1,250 | 92.4(42) | 28-1/2(723) | 77(2.2) | 3/4 NPT | 3/4(19) |
| TRC-30 | 7/8x3-1/4 or 1x4-1/4 | 3-11/32(85) | 1-3/4(44.45) | 1,550 | 36(16.3) | 29(736) | 49(1.4) | 3/8 PT | 1/2(12.7) |

Dynamic pressure: 90 PSI (0.6MPa) for all products